

SELF								
S6 1+6°C								
Model	Lenght x Depth	Volum	Doors	Model	Power (W)	Supply (V)	Light (W)	Heat. Elem. (W)
APV1/80	830x830	1.40	1	GEP 75	1440	220-1	116	124
APV2/80	1630x830	2.70	2	GEP 110	1720	220-1	174	238
APV3/80	2430x830	4.10	3	GEP 210	2440	380-3	232	355
APV4/80	2440x830	5.40	4	GEP 230	2810	380-3	348	476
CPV1/120	2450x1230	2.10	1	GEP 75	1440	220-1	116	124
CPV2/120	2460x1230	4.10	2	GEP 110	1720	220-1	174	238
CPV3/120	2470x1230	6.10	3	GEP 210	2440	380-3	232	355
CPV4/120	2480x1230	8.10	4	GEP 230	2810	380-3	348	476
S10 -18-20°C								
Model	Lenght x Depth	Volum	Doors	Model	Power (W)	Supply (V)	Light (W)	Heat. Elem. (W)
ANV1/80	2490x830	1.40	1	01/01/70	1100	220-1	116	263
ANV2/80	2500x830	2.70	2	01/01/00	2100	380-3	174	383
ANV3/80	2510x830	4.10	3	01/01/00	2610	380-3	232	506
CPV1/80	2520x1230	2.10	1	01/01/00	1630	380-3	116	263
CPV2/80	2530x1230	4.10	2	01/01/00	2100	380-3	174	383
CPV3/80	2540x1230	6.10	3	01/01/00	2610	380-3	232	506